

PLIO-SPEED

Material: polyamide 6
O-ring: polychloroprene
Colour: light grey (RAL 7035)
Protection rating: IP 68
Temperature range: -20 to +100°C

Specifications: Cable glands for quick assembly WITHOUT THREAD

Advantages:

- Mounting 3 seconds = 85% time saving compared to conventional cable gland.
- Mounting plate drilled facade = internal thread and access housing unnecessary.
- Securing sustainable even under vibration (no risk of loosening or loss against the nut).
- Clamp for fast and comfortable mounting = limited effort.
- For wall 1 to 2.5 mm (grey collar) or 2.5 to 4 mm (green collar).

Other colours, sizes and thickness's on request.



type	art. no.	cable Ø mm	hole Ø mm	wall thickness mm	colour collar		Insert (to be ordered separately)
PLIO-SPEED M12/2,5	0636 1001 025	4 - 6,5	12,4	1 - 2,5	●	50	0636 1102 000
PLIO-SPEED M12/4	0636 1002 025			2,5 - 4	●	50	
PLIO-SPEED M16/2,5	0636 1003 025	6 - 9,5	16,4	1 - 2,5	●	50	0636 1103 000
PLIO-SPEED M16/4	0636 1004 025			2,5 - 4	●	50	
PLIO-SPEED M20/2,5	0636 1005 025	7 - 12	20,4	1 - 2,5	●	50	0636 1104 000
PLIO-SPEED M20/4	0636 1006 025			2,5 - 4	●	50	
PLIO-SPEED M25/2,5	0636 1007 025	11 - 16	25,4	1 - 2,5	●	25	0636 1105 000
PLIO-SPEED M25/4	0636 1008 025			2,5 - 4	●	25	
PLIO-SPEED tool	0636 1101 000					1	
Insert PLIO-SPEED M12	0636 1102 000					1	
Insert PLIO-SPEED M16	0636 1103 000					1	
Insert PLIO-SPEED M20	0636 1104 000					1	
Insert PLIO-SPEED M25	0636 1105 000					1	



Operating instruction

INSERT PLIO-SPEED on the tool to the stop on the metal cone.

PLIO-SPEED mounted on the tool in the hole.

OPERATING-REMOVE

Squeeze the handles of the pliers and release. Remove the tool.



Operating instruction
in video